

# Environmental Product Declaration

In accordance with ISO 14025:2006 and EN 15804:2012+A2:2019/AC:2021 for:

## **MP 55<sup>®</sup>** from Knauf Orbond

Programme:

Programme operator:

EPD registration number:

Publication date:

Valid until:

The International EPD<sup>®</sup> System, [www.environdec.com](http://www.environdec.com)

EPD International AB

S-P-09661

29/06/2023

29/06/2023

An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at [www.environdec.com](http://www.environdec.com)



## General information

### Programme information

<b>Programme:</b>	The International EPD® System
<b>Address:</b>	EPD International AB Box 210 60 SE-100 31 Stockholm Sweden
<b>Website:</b>	<a href="http://www.environdec.com">www.environdec.com</a>
<b>E-mail:</b>	<a href="mailto:info@environdec.com">info@environdec.com</a>

### Accountabilities for PCR, LCA and independent, third-party verification

#### Product Category Rules (PCR)

CEN standard EN 15804 serves as the Core Product Category Rules (PCR)

Product Category Rules (PCR): 2019:14, Construction products, version 1.2.5, UN CPC 375

PCR review was conducted by: *The Technical Committee of the International EPD® System. A full list of members available on [www.environdec.com](http://www.environdec.com).*

*The review panel may be contacted via [info@environdec.com](mailto:info@environdec.com)*

*Chair of the PCR review: Claudia A. Peña*

#### Life Cycle Assessment (LCA)

LCA accountability: *Shai Ben Aharon, KVS*

#### Third-party verification

Independent third-party verification of the declaration and data, according to ISO 14025:2006, via:

☒ EPD verification by individual verifier

Third-party verifier: *Ruben Carnerero*

Approved by: The International EPD® System

Procedure for follow-up of data during EPD validity involves third party verifier:

☒ Yes ☐ No

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but registered in different EPD programmes, or not compliant with EN 15804, may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully-aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterisation factors); have equivalent content declarations; and be valid at the time of comparison. For further information about comparability, see EN 15804 and ISO 14025.

## Company Info

"ORBOND Gypsum Industries and Products Ltd". provides a variety of solutions for the construction industry. Thanks to the quality of its products, its professional knowledge, and its commitment to its customers and to the quality of the environment, Orbond has become a leader in its field in the Israeli market from the day it was founded until today.

The Orbond factory was established in Israel in 1993, and since 1998 Orbond has enjoyed the professional support of the German parent company KNAUF, a world leader in the gypsum industry, and operates approximately 320 factories which are located in 90 countries on five continents.

All the products are "MADE IN ISRAEL" and have ISO 9001 quality system management certification, ISO 14001, Environmental management, ISO 18001 And in addition, there is a green note for all products as part of the platinum certificate.

Product-related or management system-related certifications: Knauf Orbond considers sustainability to be a core value. It prefers building materials that has won sympathy among environmental authorities around the world and their products are defined as green building products.

The gypsum plasters produced by Knauf Orbond meet also the requirements of the Israeli standard 3970 for dry mixtures for construction, Israeli standard 5075 and have the green label mark by the standard institution of Israel

## Environmental Policy

Gypsum is Gypsum plaster considered a preferred construction material that wins sympathy among environmental authorities around the world and is defined as a green construction product.

Gypsum is a natural material that does not contain toxic and harmful substances, it can be recycled, and its construction produces almost no waste.

Orbond has a variety of products with a green note, among them: plasterboards, gypsum-based plasters and more. The materials are environmentally friendly and do not emit hazardous substances.

Name and location of production site(s): Knauf Orbond manufacturing site is located in the industrial area of Alon Tavor, located in Afula, Israel.

### Product information

Product: MP 55

Product identification: Gypsum plasters.

Product description:

- MP 55 – the application of the MP 55 gypsum plaster is for the use in a machine for plaster spraying. This plaster has an excellent adhesion ability. It is especially suited for areas of a building with limited ventilation conditions e.g., basements and underground parking lots. It is fit to use for internal use only and can be applied on walls, ceilings, concrete blocks, cast-in-place concrete and more. The MP 55 plaster is also fit to use for manual application. It has the unique features of not cracking, drying homogeneously even with limited ventilation conditions and it gives a perfect finish.

### Specifications:

Name of Product	MP 55
Compression strength [MPa]	>2
Adhesive strength [MPa]	>0.1
Typical consumption	10 kg /m <sup>2</sup> for 10 mm width
Color	White

Product test standard:

The product meets the Israeli standard 3970 part 1 and EN 13279-1.

UN CPC code: 37530 – Articles of plaster or of compositions based on plaster.

Geographical scope: The study represents the manufacturing of gypsum plasters in Knauf Orbond's manufacturing factory in the industrial area of Alon Tavor, located in Afula, Israel. The end-of-life scenario of the products is demolition and recycling in Israel, according to market research that was conducted.

### **LCA information**

Functional unit / declared unit: 1 kg of Gypsum Plaster

Reference service life: The Reference Service Lives result from the application areas in accordance with the / BBSR Service Life/ is as follows: a service life of at least 50 years can be considered for gypsum standard interior plasters. There are no influences on ageing when the recognized rules of technology are applied (code 345.211 for "stucco, lime-gypsum plaster" in the BBSR2017).

Time Representativeness: The time coverage of the LCA's data is from January 2021 to December 2021.

Database(s) and LCA software used: The software used is SimaPro, Analyst 9.4.0.2. The database used is the Ecoinvent database v3.8 (2021) using the cut-off by classification approach (SCLCI, 2017).

Description of system boundaries:

Cradle to gate with modules C1 –C4 and module D (A1 –A3 + C + D).

Electricity grid CO<sub>2</sub> coefficient<sub>net</sub>: the CO<sub>2</sub> coefficient of the electricity grid is 0.648 kg CO<sub>2</sub>-eq/kWh (2020) based on the renewable and non-renewable fuel sources in Israel.

Manufacturer's contact information:

Address: Alon Tavor Industrial Area, Afula 18000, Israel.

Phone Number: +972-072-3945095

Email: office@knauf.com

Website: <https://www.orbond.co.il/>

Name and contact information of the LCA practitioner: Shai Ben Aharon [shai@kvs.co.il](mailto:shai@kvs.co.il) of KVS.

Assumptions: The plasters packaging was assumed to be the same for all of the plasters and was calculated based on the relative amount per declared unit of the plaster in a bag and number of bags in a pallet.

The primary energy of raw materials was calculated for all renewable and non-renewable raw materials that had LHV value sources.

The End of life scenario was based on the recycling percentage of gypsum plasterboards in Israel (3%).

Allocations: In this study, as per EN 15804, allocation is conducted in the following order:

1. Allocation should be avoided if possible.
2. Allocation should be based on physical properties (e.g. mass, volume) when the difference in revenue is small.
3. Allocation should be based on economic values.

Overall and in general, allocations were avoided whenever possible. Nevertheless, allocations were made in the general energy usage.

Allocation used in Ecoinvent 3.8 environmental data sources follows the methodology 'allocation, cut-off by classification'. This methodology is in line with the requirements of the EN 15804 standard.

Cut-off rules: The study does not exclude any modules or processes which are stated mandatory in the EN 15804:2012+A2:2019 and the applied PCR of the EPD International Institution. The study does not exclude any hazardous materials or substances. The study includes all major raw materials and energy consumption. All inputs and outputs of the unit processes with available data are included in the calculation. There is no neglected unit process of more than 1% of total mass or energy flows, and in fact components with a share of even less than 1% are included.

Background Database: The EPD is based on the primary production data of Knauf-Orbond. The background database is Ecoinvent database v3.8 (2021). Since there are several missing datasets for Israel, background data for larger areas in which Israel is included in was used for a small part of the life cycle inventory. The electricity mix of the high voltage electricity grid according to 2020 data is given by a formal report from the ministry of energy in Israel and the water grid is modeled according to the water sources in Israel.



Modules declared, geographical scope, share of specific data (in GWP-GHG results) and data variation (in GWP-GHG results):

	Product stage			Construction process stage		Use stage							End of life stage				Resource recovery stage
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	X	X	X	X	X
Geography	IL EUR Global	IL EUR Global	IL										IL	IL	IL	IL	IL
Specific data used	>90%					-	-	-	-	-	-	-	-	-	-	-	-
Variation – products	0%					-	-	-	-	-	-	-	-	-	-	-	-
Variation – sites	0%					-	-	-	-	-	-	-	-	-	-	-	-

**Module A1 – Supply of raw materials:** The declared Knauf Orbond gypsum plasters consist of a natural gypsum mix with additives. The raw materials supply includes raw material extraction/preparation or pre-treatment processes before production that are taken into account in this study. The raw materials of packaging i.e., wooden pallets, paper sacks and polyethylene are also included in this module.

**Module A2 – Transport of raw materials:** Natural gypsum is extracted from mines abroad in a nearby country to the manufacturing sites. Accordingly, transport distances are short and done by ships and trucks. Further raw materials are supplied from manufacturers within Israel or from other European countries.

**Module A3 – Manufacturing:** The manufacturing includes stucco mixing with calcite and additives. The end products are packaged into sacks. Powder gypsum products must be protected from moisture absorption, therefore during transportation and storage they are stored in enclosed spaces. Electric energy, natural gas and diesel are consumed during the manufacturing process.

#### End-of-Life stage (C1-C4):

**Module C1 – De-construction:** Demolition of plasters takes place with the whole demolition of the building/construction. Thus it is assumed that energy used for the demolition of gypsum plasters has minor significance and the environmental impact of this module is set to be zero.

At the end-of-life, in the demolition phase 100% of the waste is assumed to be collected as mixed construction waste.

**Module C2 – Transportation:** Transportation distance to the closest disposal area is estimated as 50 km by a 16-32 tonne lorry, which is the most common.

**Module C3 – Waste processing** According to interviews with industry executives that manage the construction waste in Israel (GREENMIX, Negevecology), there is no any significant processing of the construction waste and especially not for the gypsum residues, therefore the environmental impact of this module is set to be zero.

**Module C4 – Disposal:** 100% of the gypsum plasters will be landfilled.

### Resource-Recovery stage (D):

**Module D – Reuse-Recovery-Recycling potential:** It is assumed and modeled that there is no reuse or recovery of the products.

## Content information

Product components	Weight, kg	Post-consumer material, weight-%	Biogenic material, weight-% and kg C/kg
Stucco	78-90	0	0
Limestone	9-19	0	0
Additives	1-2.5	0	0
TOTAL	100	0	0
Packaging materials	Weight, kg	Weight-% (versus the product)	Weight biogenic carbon, kg C/kg
Paper bag	<0.1	<0.1	<0.1
PE cover	<0.1	<0.1	0
Wooden pallet	<0.1	<0.1	<0.1
TOTAL	<0.1	<0.1	<0.1

Dangerous substances from the candidate list of SVHC for Authorisation	EC No.	CAS No.	Weight-% per functional or declared unit
ND	ND	ND	ND

## Environmental Information

The EPD is for a specific product – **Environmental impacts of 1 kg MP 55 Plaster**

### Potential environmental impact – mandatory indicators according to EN 15804

Indicator	Unit	A1-A3	C1	C2	C3	C4	D
GWP-fossil	kg CO <sub>2</sub> eq.	8.34E-02	0	8.50E-03	0	9.12E-03	0
GWP-biogenic	kg CO <sub>2</sub> eq.	-2.27E-03	0	4.60E-06	0	6.56E-06	0
GWP – luluc	kg CO <sub>2</sub> eq.	1.26E-04	0	3.56E-06	0	5.34E-06	0
GWP – total	kg CO <sub>2</sub> eq.	8.13E-02	0	8.51E-03	0	9.13E-03	0
ODP	kg CFC 11 eq.	9.07E-09	0	1.83E-09	0	2.99E-09	0
AP	mol H <sup>+</sup> eq.	3.77E-04	0	2.50E-05	0	9.03E-05	0
EP – freshwater	kg PO <sub>4</sub> eq.	8.44E-05	0	2.21E-07	0	1.88E-07	0
EP – freshwater	kg P eq.	2.76E-05	0	7.21E-08	0	6.13E-08	0
EP – marine	kg N eq.	3.50E-04	0	4.98E-06	0	3.55E-05	0
EP - terrestrial	mol N eq.	8.35E-04	0	5.56E-05	0	3.90E-04	0
POCP	kg NMVOC eq.	3.30E-01	0	2.08E-05	0	1.10E-04	0
ADP-minerals&metals*	kg Sb eq.	8.21E-01	0	1.26E-01	0	2.01E-01	0
ADP-fossil*	MJ	1.58E-03	0	2.95E-08	0	1.40E-08	0
WDP*	m <sup>3</sup>	1.42E-02	0	4.40E-04	0	6.71E-03	0
Acronyms	GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption						

\* Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.

### Potential environmental impact – additional mandatory and voluntary indicators

Indicator	Unit	A1-A3	C1	C2	C3	C4	D
GWP-GHG <sup>1</sup>	kg CO <sub>2</sub> eq.	8.36E-02	0	8.50E-03	0	9.12E-03	0

<sup>1</sup> This indicator accounts for all greenhouse gases except biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. As such, the indicator is identical to GWP-total except that the CF for biogenic CO<sub>2</sub> is set to zero.



## Use of resources

Indicator	Unit	A1-A3	C1	C2	C3	C4	D
PERE	MJ	1.02E-01	0	1.24E-01	0	2.00E-01	0
PERM	MJ	1.31E-01	0	1.53E-03	0	1.80E-03	0
PERT	MJ	2.33E-01	0	5.65E-06	0	2.65E-05	0
PENRE	MJ	1.11E+00	0	4.28E-04	0	3.94E-04	0
PENRM	MJ	4.30E-02	0	2.13E-04	0	2.26E-04	0
PENRT	MJ	1.15E+00	0	8.25E-04	0	8.47E-04	0
SM	kg	0	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0
FW	m <sup>3</sup>	3.98E-04	0	1.45E-05	0	1.61E-04	0
Acronyms	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy re-sources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water						

## Waste production and output flows

### Waste production

Indicator	Unit	A1-A3	C1	C2	C3	C4	D
Hazardous waste disposed	kg	2.01E-06	0	3.32E-07	0	3.73E-07	0
Non-hazardous waste disposed	kg	1.78E-02	0	6.50E-03	0	1.00E+00	0
Radioactive waste disposed	kg	3.17E-06	0	8.20E-07	0	1.34E-06	0

### Output flows

Indicator	Unit	A1-A3	C1	C2	C3	C4	D
Components for re-use	kg	6.70E-04	0	0	0	0	0
Material for recycling	kg	0	0	0	0	0	0
Materials for energy recovery	kg	0	0	0	0	0	0
Exported energy, electricity	MJ	0	0	0	0	0	0
Exported energy, thermal	MJ	0	0	0	0	0	0

# References

General Programme Instructions of the International EPD® System. Version 4.0.  
The PCR of EN 15804:2012+A2:2019/AC:2021

A national-level LCA of a water supply system in a Mediterranean semi-arid climate—Israel as a case study / auth. Thoma Noa Meron & Vered Blass & Greg. - Germany : The International Journal of Life Cycle Assessment, 2020.

BRE Global Product Category Rules (PCR) For Type III EPD of Construction Products to EN 15804+A2 / auth. Global BRE. - Watford : BRE Group, 2020.

Composition and Leaching of FGD Gypsum and Mined Gypsum / auth. Ladwig K.. - Palo Alto, CA : EPRI, 2011.

EN 15804:2012+A2 - Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products

Gypsum as an Agricultural Amendment - General Use Guidelines / auth. Dick Liming Chen and Warren A.. - Ohio : Ohio State University.

ISO 14025:2010 Environmental labels and declarations – Type III environmental declarations principles and procedures.  
ISO 14040:2006 Environmental management. Life cycle assessment principles and frameworks.  
ISO 14044:2006 Environmental management. Life cycle assessment requirements and guidelines.

Life Cycle Assessment Quantitative Approaches for Decisions That Matter / auth. H. Scott Matthews Chris T. Hendrickson and Deanna H. Matthews. - 2015.

Life cycle energy and material flow implications of gypsum plasterboard recycling in the European Union / auth. Ana Jimenez Rivero Roger Sathre, Justo Garcia Navarro. - [s.l.] : ELSEVIER, 2015.

SimaPro Database Manual - Methods Library / auth. Sustainability PRé. - 2020.

System Models / auth. Ecoinvent // Ecoinvent. - <https://ecoinvent.org/the-ecoinvent-database/system-models/>.

## Contact information

Programme operator:  **EPD<sup>®</sup>**

EPD owner:   
Knauf Orbond  
<https://www.orbond.co.il/>  
[orbond@orbond.co.il](mailto:orbond@orbond.co.il)  
T: +972-4-6521141

LCA author:   
KVS  
<http://www.kvs.co.il/>  
[info@kvs.co.il](mailto:info@kvs.co.il)  
03-917 2202

3rd party verifie Ruben Carnerero  
[r.carnerero@ik-ingenieria.com](mailto:r.carnerero@ik-ingenieria.com)